

MODEL: GT-BS03

Oder Code	GT-BS03 (Old Model: GT3510)
LED	5W/Pcs Cree
Row	Single Row
Operating Voltage	10-30V DC
Operating Temp	-40~+60 °Celcius
Beam Pattern	Spot, Flood, Combo
Color Temperature	6000K
Lifetime	30000+h
Lens Material	Polycarbonate
Housing Material	Aluminum
Coating Powder	Sand Black
Mounting System	304 Stainless Steel Bottom Mount /Aluminum Side Mount
Pressure Equalization Vent	Yes
Waterproof Rate	IP67
EMC Protection	ECE R10
Beam Type Protection	ECE R112



MODEL	Size	Watt	AMP Draw	Leds	Theoretical Lumen	Cable Length	Net Weight	Package Standard
GT-BS03-6L	7.90"	30W	1.50A@12V, 0.75A@24V	6PCS*5W	2200Lm	400mm	0.69Kg/Pcs	10Pcs/Carton
GT-BS03-10L	11.80"	50W	3.00A@12V, 1.50A@24V	10PCS*5W	3666Lm	400mm	0.99Kg/Pcs	10Pcs/Carton
GT-BS03-20L	21.60"	100W	5.00A@12V, 2.50A@24V	20PCS*5W	7333Lm	600mm	1.10Kg/Pcs	5Pcs/Carton
GT-BS03-30L	31.30"	150W	7.50A@12V, 3.75A@24V	30PCS*5W	10980Lm	800mm	2.56Kg/Pcs	5Pcs/Carton
GT-BS03-40L	41.30"	200W	10.00A@12V, 5.00A@24V	40PCS*5W	14640Lm	800mm	1.50Kg/Pcs	5Pcs/Carton
GT-BS03-50L	51.10"	250W	12.50A@12V, 6.25A@24V	50PCS*5W	18300Lm	800mm	2.20Kg/Pcs	5Pcs/Carton

